


MS M350



*HIGH-SPEED VGA-FORMAT SCIENTIFIC
MULTISPECTRAL THERMAL IMAGING*

KEY FEATURES



MULTISPECTRAL CAPABILITIES



HIGH DYNAMIC RANGE



ADVANCED CALIBRATION



HIGH SENSITIVITY


The MS-IR infrared camera allows the scene to be split into eight different spectral bands rather than only one broadband image, thus enabling spectral signature analysis. The filter wheel is a fast-rotating mechanism designed to maximize the cameras' frame rate. Rotating speed is adjustable up to 105 Hz per filter, allowing a frame rate up to 2 900 fps in a synchronised mode.



MS M350



Multispectral image of burning wood crib



Typical MWIR combustion spectrum and filters

SPECIFICATIONS

Detector Type	Cooled InSb
Detector Format	640 × 512 pixels
Spectral Range	1.5 μm to 5.4 μm
Detector Pitch	15 μm
Aperture Size	F/3
Maximum Frame Rate in Full Window (Static Filter Wheel Mode)	355 Hz
Maximum Frame Rate in Subwindow (Static Filter Wheel Mode)	4 980 Hz @ 132 × 4
Maximum Frame Rate in Rotating Filter Wheel Mode	800 Hz
Typical NETD	20 mK
Exposure Time	0.5 μs to full frame rate
Lens Mount	Bayonet

sales@telops.com



telops.com

EXOSSENS
REVEAL THE INVISIBLE